

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.05.2023

Version number 2305 (replaces version 2206)

Revision: 02.05.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **MANNOL 9892 M-40 Lubricant (smart) 400ml**

UFI: 3VDV-Q03Q-E00R-J6AH

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Lubricant

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SCT-Vertriebs GmbH

Feldstrasse 154

22880 WEDEL

DEUTSCHLAND

+49 (0)4103 1211 0

info@sct-germany.de

Further information obtainable from: Product safety department.

1.4 Emergency telephone number:

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 2 H223-H229 Flammable aerosol. Pressurised container: May burst if heated.



GHS08 health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.05.2023

Version number 2305 (replaces version 2206)

Revision: 02.05.2023

Trade name: MANNOL 9892 M-40 Lubricant (smart) 400ml

(Contd. of page 1)

· **Hazard pictograms**



GHS02 GHS05 GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**

Distillates (petroleum), hydrotreated light
Dodecenylsuccinic acid

· **Hazard statements**

H223-H229 Flammable aerosol. Pressurised container: May burst if heated.
H318 Causes serious eye damage.
H304 May be fatal if swallowed and enters airways.
H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P273 Avoid release to the environment.
P280 Wear eye protection / face protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331 Do NOT induce vomiting.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405 Store locked up.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 64742-47-8 EINECS: 265-149-8	Distillates (petroleum), hydrotreated light Flam. Liq. 3, H226; Asp. Tox. 1, H304	38–42.4%
CAS: 106-97-8 EINECS: 203-448-7	butane, pure Flam. Gas 1A, H220; Press. Gas (Comp.), H280	16–21%
CAS: 29658-97-7 EINECS: 249-757-0	Dodecenylsuccinic acid Alternative CAS number: 11059-31-7 Eye Dam. 1, H318; Aquatic Chronic 3, H412	5–9.5%

(Contd. on page 3)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.05.2023

Version number 2305 (replaces version 2206)

Revision: 02.05.2023

Trade name: MANNOL 9892 M-40 Lubricant (smart) 400ml

(Contd. of page 2)

CAS: 74-98-6 EINECS: 200-827-9	propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	4–9%
CAS: 111-76-2 EINECS: 203-905-0	2-butoxyethanol Acute Tox. 3, H311; Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319 ATE: LD50 oral: 1,200 mg/kg	1–5%
CAS: 124-30-1 EINECS: 204-695-3	Octadecylamine STOT RE 2, H373; Asp. Tox. 1, H304; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=10); Skin Irrit. 2, H315	0.05–0.15%

· Not dangerous substances

CAS: 67254-74-4 EC number: 614-042-8	Naphthenic oils	8–13%
---	-----------------	-------

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** A person vomiting while laying on their back should be turned onto their side.

· 4.2 Most important symptoms and effects, both acute and delayed

Nausea
Coughing
Headache
Dizziness

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media**· Suitable extinguishing agents:**

CO₂. Do not use water.
Use fire extinguishing methods suitable to surrounding conditions.
Foam
Fire-extinguishing powder
Sand

· For safety reasons unsuitable extinguishing agents: Water**· 5.2 Special hazards arising from the substance or mixture** No further relevant information available.**· 5.3 Advice for firefighters****· Protective equipment:** No special measures required.**· Additional information**

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

(Contd. on page 4)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.05.2023

Version number 2305 (replaces version 2206)

Revision: 02.05.2023

Trade name: **MANNOL 9892 M-40 Lubricant (smart) 400ml**

(Contd. of page 3)

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Particular danger of slipping on leaked/spilled product.

Wear protective clothing.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Use neutralising agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions: Keep container tightly sealed.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane, pure (21.0%)

OEL | Short-term value: 1000 ppm

74-98-6 propane (9.0%)

OEL | Asphx

111-76-2 2-butoxyethanol (5.0%)OEL | Short-term value: 246 mg/m³, 50 ppmLong-term value: 98 mg/m³, 20 ppm

Sk, IOELV

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.05.2023

Version number 2305 (replaces version 2206)

Revision: 02.05.2023

Trade name: MANNOL 9892 M-40 Lubricant (smart) 400ml

(Contd. of page 4)

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**
 - Keep away from foodstuffs, beverages and feed.
 - Immediately remove all soiled and contaminated clothing
 - Wash hands before breaks and at the end of work.
 - Store protective clothing separately.
 - Avoid contact with the eyes.
 - Avoid contact with the eyes and skin.
- **Respiratory protection:**
 - In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye/face protection**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Colour:** Brown
- **Odour:** Characteristic
- **Odour threshold:** Not determined.
- **Melting point/freezing point:** Undetermined.
- **Boiling point or initial boiling point and boiling range** Not applicable, as aerosol.
- **Flammability** Not applicable.

(Contd. on page 6)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.05.2023

Version number 2305 (replaces version 2206)

Revision: 02.05.2023

Trade name: MANNOL 9892 M-40 Lubricant (smart) 400ml

(Contd. of page 5)

· Lower and upper explosion limit	
· Lower:	0.5 Vol %
· Upper:	6.5 Vol %
· Flash point:	Not applicable, as aerosol.
· Auto-ignition temperature:	210 °C
· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C:	2 hPa
· Density and/or relative density	
· Density at 20 °C:	0.83 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.

9.2 Other information

· Appearance:	
· Form:	Liquid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Not determined.
· Solvent content:	
· Organic solvents:	5–14 %
· VOC (EC)	21–35 %
· Solids content:	0.1–0.2 %
· Change in condition	
· Evaporation rate	Not applicable.

Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	
Flammable aerosol. Pressurised container: May burst if heated.	
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void

(Contd. on page 7)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.05.2023

Version number 2305 (replaces version 2206)

Revision: 02.05.2023

Trade name: MANNOL 9892 M-40 Lubricant (smart) 400ml

(Contd. of page 6)

- | | |
|----------------------------------|------|
| · Organic peroxides | Void |
| · Corrosive to metals | Void |
| · Desensitised explosives | Void |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
Carbon monoxide
Aldehyde
Poisonous gases/vapours
Carbon dioxide

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

ATE (Acute Toxicity Estimates)

Oral	LD50	29,600–148,000 mg/kg (rat)
Dermal	LD50	8,000–40,000 mg/kg (rab)
Inhalative	LC50/4 h	220–1,100 mg/l

106-97-8 butane, pure

Inhalative	LC50/4 h	658 mg/l (rat)
------------	----------	----------------

111-76-2 2-butoxyethanol

Oral	LD50	1,200 mg/kg (ATE) 1,480 mg/kg (rat)
Dermal	LD50	400 mg/kg (rab)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**
Causes serious eye damage.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard**
May be fatal if swallowed and enters airways.

(Contd. on page 8)

IE



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.05.2023

Version number 2305 (replaces version 2206)

Revision: 02.05.2023

Trade name: MANNOL 9892 M-40 Lubricant (smart) 400ml

(Contd. of page 7)

11.2 Information on other hazards**Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity**Aquatic toxicity:** No further relevant information available.**12.2 Persistence and degradability** No further relevant information available.**12.3 Bioaccumulative potential** No further relevant information available.**12.4 Mobility in soil** No further relevant information available.**12.5 Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Endocrine disrupting properties**

For information on endocrine disrupting properties see section 11.

12.7 Other adverse effects**Remark:** Harmful to fish**Additional ecological information:****General notes:**

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even extremely small quantities leak into the ground.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

13.1 Waste treatment methods**Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

HP3	Flammable
HP6	Acute Toxicity
HP14	Ecotoxic

Uncleaned packaging:**Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN number or ID number**ADR, IMDG, IATA**

UN1950

14.2 UN proper shipping name**ADR**

1950 AEROSOLS

IMDG, IATA

AEROSOLS

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.05.2023

Version number 2305 (replaces version 2206)

Revision: 02.05.2023

Trade name: MANNOL 9892 M-40 Lubricant (smart) 400ml

(Contd. of page 8)

· **14.3 Transport hazard class(es)**

· **ADR, IMDG, IATA**



· **Class** 2 Gases.
 · **Label** 2.1

· **14.4 Packing group**

· **ADR, IMDG, IATA** III

· **14.5 Environmental hazards:**

Not applicable.

· **14.6 Special precautions for user**

Warning: Gases.

· **Hazard identification number (Kemler code):** -

· **EMS Number:**

F-D,S-U

· **Stowage Code**

SW1 Protected from sources of heat.
 SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

· **Segregation Code**

SG69 For AEROSOLS with a maximum capacity of 1 litre:
 Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.
 For AEROSOLS with a capacity above 1 litre:
 Segregation as for the appropriate subdivision of class 2.
 For WASTE AEROSOLS:
 Segregation as for the appropriate subdivision of class 2.

· **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

· **Transport category**

3

· **Tunnel restriction code**

E

· **IMDG**

· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

· **UN "Model Regulation":**

UN 1950 AEROSOLS, 2.1

(Contd. on page 10)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.05.2023

Version number 2305 (replaces version 2206)

Revision: 02.05.2023

Trade name: MANNOL 9892 M-40 Lubricant (smart) 400ml

(Contd. of page 9)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P3a FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

National regulations:

- **Additional classification according to Decree on Hazardous Materials, Annex II:** Carcinogenic hazardous material group III (dangerous).

Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H220 Extremely flammable gas.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H311 Toxic in contact with skin.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.

(Contd. on page 11)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.05.2023

Version number 2305 (replaces version 2206)

Revision: 02.05.2023

Trade name: MANNOL 9892 M-40 Lubricant (smart) 400ml

(Contd. of page 10)

H332 Harmful if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

- **Department issuing SDS:** Product safety department.
- **Date of previous version:** 23.06.2022
- **Version number of previous version:** 2206
- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 2: Aerosols – Category 2

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 3: Acute toxicity – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

- *** Data compared to the previous version altered.**